



when only **perfection** will do

TERRASPORT  
**REFUSEMATE**



**Powerful V-Twin 4 Cycle Air Cooled 16hp Engine**

**20 MPH Maximum Speed**

**Automatic Transmission, Multi-Leaf Spring Dual Shock Suspension & 4-Wheel Hydraulic Drum Brakes**

**Tough Fiberglass Cowl, Fenders & Hood**

**Twin Bucket Seats (cool white)**

**2.0 Cubic Yard, Water Tight 14 Gauge Steel Refuse Dump Box with 2 GPM, 12 Volt Hydraulic System & Heavy Duty 2-Stage Cylinder**

**Parks - Recreational Facilities**

**Colleges - Universities**

**Sports Turf - Athletic Complexes**

**Municipal - Commercial - Industrial**



**Full seam welded construction**

**Electric solenoid switch controlled dumping action**



**Welded tubular steel frame construction and carefully engineered suspension provide maximum riding comfort with a 1500 lb. payload capacity. The cab-over design maximizes operator visibility and turn radius.**



**No vehicle auxiliary hydraulics required**

**REFUSEMATE**

**The new TerraSport RefuseMate is a powerful turf utility vehicle specially accessorized with a refuse collection container for clean-up around parks, camp grounds, athletic facilities or virtually any off road area. Its mid-mounted engine provides a safe, low center of gravity. 2.0 cubic yard, 1000 lb. capacity container. 12 volt electric hydraulic system is complete with oil reservoir, 2 GPM pump and sturdy 2-stage dump cylinder. Low profile box reduces manual lifting when loading, and its flared design assures complete clean out when dumping. Now, Broyhill can make you and your environment look good.**

### TerraSport RefuseMate Specifications

#### Vehicle:

|                     |                                                                               |
|---------------------|-------------------------------------------------------------------------------|
| Engine              | 16hp Briggs V-Twin cyl. 4cycle, OHV, air cooled gas                           |
| Drive System        | Automatic (CVT) transmission* (2 wheel drive)                                 |
| Suspension: Rear    | Heavy duty multi-leaf spring                                                  |
| Front               | Captive multi-leaf springs, dual shocks                                       |
| Fuel Capacity       | 8 gallons                                                                     |
| Brakes              | Four wheel, hydraulic drum, mechanical park brake                             |
| Electrical          | 12 volt battery, 15 amp, 12 volt elec. neutral start, twin halogen headlights |
| Body                | Fiberglass cowl, fenders & hood                                               |
| Steering            | Front wheel power steering: automotive type 13" steering wheel                |
| Main Frame          | Welded tubular steel frame construction; mid engine placement                 |
| Tires/Wheels: Front | 22.5 X 10 – 8 HD Field Trax TL                                                |
| Rear                | 25 X 13 – 9 HD Field Trax TL                                                  |
| Drive Controls      | Foot operated accelerator, brake pedal and shift lever with Forward/Reverse   |
| Seat                | 2 Bucket                                                                      |

#### Dimensions:

|                          |                        |
|--------------------------|------------------------|
| Payload Capacity         | 1500 lbs**             |
| Towing Capacity          | 1500 lbs               |
| Weight w/refuse box      | 2.0 cu.yd. = 1760 lbs. |
| Rear Tread Centers       | 49"                    |
| Front Tread Centers      | 41"                    |
| Wheelbase                | 66"                    |
| Overall Length           | 114" w/o refuse box    |
| Inside Clearance Circle  | 8'                     |
| Outside Clearance Circle | 20'                    |
| Height at Steering Wheel | 4'                     |
| Floorboard Height        | 15"                    |
| Minimum Ground Clearance | 7"                     |

#### Refuse Box:

|                |                           |
|----------------|---------------------------|
| Box Dimensions | 2.0 cubic yards, 61" wide |
| Hydraulics     | 12 Volt, 2-GPM            |

\*With differential lock

\*\*Includes 250 lb. operator, 250 lb. passenger & accessories.

Options Include: Speedometer, Tachometer, Hand Throttle Control, Accessory Light Kit, Reverse Alarm

For more information, contact:

**The Broyhill Company - Dakota City NE 68731**

One North Market Square, Box 475

Phone: 402.987.3412 FAX: 402.987.3601

Sales Order Placement: 800.228.1003, ext. 34

www.Broyhill.com E-MAIL: Broyhillsal@aol.com

Copyright 09/02

**Distributed By:**



**Now, eliminating litter keeps you in the drivers seat with the powerful TerraSport VacMate.**

**Since 1946, it's Broyhill, Making You Look Good.**



**The spring arm mounted suction hose with electric power assist makes easy clean up of virtually any facility, including factories and industrial areas.**

### TerraSport VacMate Specifications

#### Vehicle:

|                     |                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------|
| Engine              | 16hp Briggs V-Twin cyl. 4cycle, OHV, air cooled gas                                          |
| Drive System        | Automatic (CVT) transmission* (2 wheel drive)                                                |
| Suspension: Rear    | Heavy duty multi-leaf spring                                                                 |
| Front               | Captive multi-leaf springs, dual shocks                                                      |
| Fuel Capacity       | 8 gallons                                                                                    |
| Brakes              | Four wheel, hydraulic drum, mechanical park brake                                            |
| Electrical          | 12 volt battery, 15 amp, 12 volt elec. neutral start, twin halogen headlights & strobe light |
| Body                | Fiberglass cowl, fenders & hood                                                              |
| Steering            | Front wheel power steering: automotive type 13" steering wheel                               |
| Main Frame          | Welded tubular steel frame construction; mid engine placement                                |
| Tires/Wheels: Front | 22.5 X 10 – 8 HD Field Trax TL                                                               |
| Rear                | 25 X 13 – 9 HD Field Trax TL                                                                 |
| Drive Controls      | Foot operated accelerator, and brake pedal; shift lever with forward & reverse               |
| Seat                | 2 Bucket                                                                                     |

#### Dimensions:

|                          |               |
|--------------------------|---------------|
| Payload Capacity         | 1500 lbs**    |
| Towing Capacity          | 1500 lbs      |
| Weight w/vacuum          | 1780 lbs.     |
| Rear Tread Centers       | 49"           |
| Front Tread Centers      | 41"           |
| Wheelbase                | 66"           |
| Overall Length           | 114" w/vacuum |
| Inside Clearance Circle  | 8'            |
| Outside Clearance Circle | 20'           |
| Height at Steering Wheel | 4'            |
| Floorboard Height        | 15"           |
| Minimum Ground Clearance | 7"            |

#### Vacuum:

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| Dimensions        | 51" L X 47" W X 21" H                                                    |
| Weight            | 580 lbs.                                                                 |
| Capacity          | 1 cubic yard                                                             |
| Engine            | 18 HP Gas Honda, air cooled, 12V elec. start                             |
| Housing           | 14 gauge welded steel                                                    |
| Impeller          | 19" diameter, direct drive high speed balanced                           |
| Flex Suction Hose | 8" diameter x 13' long PVC wire reinforced<br>Electric power assist lift |

\*With differential lock

\*\*Includes 250 lb. operator, 250 lb. passenger & accessories.

Options Include: Speedometer, Tachometer, Hand Throttle Control  
Accessory Light Kit, Reverse Alarm

For more information, contact:  
**Broyhill Company - Dakota City NE 68731**

One North Market Square, Box 475  
Phone: 402.987.3412 FAX: 402.987.3601  
Sales Order Placement: 800.228.1003, ext. 34  
www.Broyhill.com E-MAIL: Broyhilsal@aol.com  
Copyright 09/02

**Distributed By:**